

Contact Clean+ c32



BENEFITS

- ✓ efficient and fast dissolving of contaminations on electrical contacts
- ✓ non-conductive
- ✓ residue-free
- ✓ comes with an extra spray nozzle and extension tube

Usage



PRODUCT DESCRIPTION

BIZOL Contact Clean+ c32 is an effective solvent specially developed to clean electrical contacts. It is non-conductive and non-corrosive and leaves no residue. It has a powerful jet spray and comes with an additional spray nozzle and an extension tube in the cap for precise spraying.



Contact Clean+ c32

Available Packages

Size	Art. Nr
400 ml	80005

Technical Data

Name	Value	Method
Basis	Aliphatic Hydrocarbons with alcohol	
Propellant	Carbon dioxide	
Colour	Transparent	
Scent	Characteristic	
Relative density at 20°C	0,73 g/ml	
Refractive Index at 20°C	1,37	

Applications

Spray on switches, batteries, contact points, printed circuit board switches, multiple sockets.

How to use

The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Switch off electrical installations before treatment. Spray the parts to be treated until the contamination has disappeared. Contaminated contact cleaner should be regarded as chemical waste. Only switch on the electrical installation after evaporation of the solvent (minimum of 15 minutes).

Follow instructions

Please follow the operating instructions of the vehicle and engine manufacturer.