

Allround Gear Oil GL4 80W-90



BENEFITS

- ✓ best temperature/viscosity properties
- ✓ reduces wear and running noise
- ✓ very good anti-ageing and chemical stability

PRODUCT DESCRIPTION

BIZOL Allround Gear Oil GL4 80W-90 is a mineral high-performance transmission oil for use in spur, bevel as well as worm gears. This product is utilized in synchronized and non-synchronized manual transmissions, driving gears of construction and agricultural machinery as well as tractors.

Base Oil: Mineral

SPECIFICATIONS

API GL 4

MB 235.1

MAN M 341 E1

ZF TE-ML 06L,08,16A,17A,19A,19C

Available Packages

Size	Art. Nr
1 L	87320
20 L	87322

Technical Data

Name	Value	Method
Viscosity class SAE	80W-90	SAE J 300
Viscosity at 40 °C	203 mm²/s	ASTM D 7042
Viscosity at 100 °C	17,2 mm²/s	ASTM D 7042
Viscosity index	90	ASTM D 2270
Density at 15 °C	890 kg/m³	DIN EN ISO 12 185
Pour Point	-21 °C	ISO 3016
Flash Point (Cleveland)	230 °C	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.