

Initial HD SAE 10W-40



BENEFITS

- ✓ highly stable lubrication film
- ✓ good cold-start performance
- ✓ effective against corrosion
- ✓ engineered for mixed fleets

PRODUCT DESCRIPTION

BIZOL Initial HD SAE 10W-40 is a modern high-performance, low-friction motor oil. Modern technology in combination with unique base oils provides this product with its outstanding characteristics such as reduced friction and wear protection and helps prolonging the intervals between oil changes.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA E7, API CI-4, JASO DH-1, Global DHD-1

MB 228.3,235.28

Volvo VDS 3

Cummins CES 20076,CES 20077,CES 20078

Detroit Diesel DDC 93K215

MAN M 3275-1

Renault Truck RLD-2

MTU Type 2

Voith Retarder B

MACK EO-N

Deutz DQC III

Caterpillar ECF-2,TO-2

Allison C4

Initial HD SAE 10W-40

Available Packages

Size	Art. Nr
20 L	186032
208 L	186038

Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	SAE J 300
Viscosity at 40 °C	98,2 mm²/s	ASTM D 7042
Viscosity at 100 °C	14,3 mm²/s	ASTM D 7042
Viscosity index	154	ASTM D 2270
Density at 15 °C	870 kg/m³	DIN EN ISO 12 185
Pour Point	<-36 °C	ISO 3016
Flash Point (Cleveland)	>210 °C	ISO 2592
Colour	yellow-brown	
Total base number (TBN)	11,8 mg KOH/g	ASTM D 2896

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.