# Initial HLP-D 32 Hydraulic Oil

## BENEFITS

## PRODUCT DESCRIPTION

**BIZOL Initial HLP-D 32 Hydraulic Oil** is used for all kinds of hydraulic aggregates, for which the use of HLP-D-alloyed oils is prescribed. Mineral base oils and effective zinc-containing components ensure optimum lubrication and long-lasting protection against aging.

## Base Oil: Mineral

## SPECIFICATIONS

**DIN 51524-2, ISO 11158, ASTM D 6158, SEB 181222**



The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

# Initial HLP-D 32 Hydraulic Oil

## Available Packages

| Size | Art. Nr |
|---|---|
| 20 L | 182202 |
| 60 L | 182203 |
| 208 L | 182208 |

## Technical Data

| Name | Value | Method |
|---|---|---|
| Viscosity at 40 °C | 32 mm²/s | ASTM D 7042 |
| Viscosity at 100 °C | 5,2 mm²/s | ASTM D 7042 |
| Viscosity index | 109 | ASTM D 2270 |
| Density at 15 °C | 850 kg/m³ | DIN EN ISO 12 185 |
| Flash Point (Cleveland) | 210 °C | ISO 2592 |
| Pour Point | -36 °C | ISO 3016 |
| FZG Test A/8,3/90 | >12 | DIN 51 354/2 |

## Follow instructions

On refilling an changing the Hydraulic Oil please follow the operating instructions of the manufacturer.



The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.