# Technology 0W-20 C5

BIZOL Technology 0W-20 C5 is a specially developed, low-viscosity mid SAPS engine oil for the demanding requirements of high-performance engines from European vehicle manufacturers. A combination of unconventional base oils and modern additive technology reduces friction and ensures low fuel consumption with maximum engine performance

Can be used with:
API SQ (RC)
ACEA C5
ACEA C6
ILSAC GF-7A
MB 229.71
MB 229.72
BMW LL 17 FE+
BMW LL 14FE+
GM DEXOS D
Opel OV0401547-A20
Volvo VCC RBSO-2AE
Fiat 9.55535-GSX
Ford WSS-M2C947-B1
954-A1
962-A1
Chrysler MS-12145
VWC 53037

| Parameter | Test Method | Result |
|---|---|---|
| Viscosity class SAE | SAE J 300 | 0W-20 |
| Kinematic Viscosity @ 40°C [mm²/s] | ASTM D-7042 | 42,9 |
| Kinematic Viscosity @ 100°C [mm²/s] | ASTM D-7042 | 8,2 |
| Viscosity index | - | 169 |
| Density @ 15 °C [kg/m³] | DIN EN ISO 12 185 | 840 |
| Pourpoint [°C] | ISO 3016 | -42 |
| TBN [mg KOH/g] | ASTM D-2896 | >7,5 |

| | |
|---|---|
| 1 Liter | Art. No. 88210 |
| 5 Liter | Art. No. 88211 |
| 20 Liter | Art. No. 88212 |
| 60 Liter | Art. No. 88213 |
| 208 Liter | Art. No. 88214 |