

Allround 0W-20



BENEFITS

- ✓ Low-viscosity oil especially for Asian and American vehicles
- ✓ Standard SAPS
- ✓ Low viscosity
- ✓ Friction reduction
- ✓ Fuel economy

PRODUCT DESCRIPTION

BIZOL Allround 0W-20 is a low viscosity, standard SAPS fuel-efficient engine oil especially for gasoline engines of Asian and American vehicles. It minimizes the risk of low-speed pre-ignition (LSPI) and reduces wear during cold engine start.

Base Oil: HC-Synthetic

SPECIFICATIONS

API SP/SN Plus, ILSAC GF-6A

GM DEXOS 1 Gen. 3,6094 M

Chrysler MS-6395

Fiat 9.55535-GSX,9.55535-CR1

Ford WSS-M2C947-B1,WSS-M2C-962-A1

Allround 0W-20

Available Packages

Size	Art. Nr	Languages
4 L	85836	
5 L	85831	
5 L	35831	EN / DE / FR / ES / IR

Technical Data

Name	Value	Method
Viscosity class SAE	0W-20	SAE J 300
Viscosity at 40 °C	45,1 mm²/s	ASTM D 7042
Viscosity at 100 °C	8,5 mm²/s	ASTM D 7042
Viscosity index	169	ASTM D 2270
Density at 15 °C	840 kg/m³	DIN EN ISO 12 185
Pour Point	-48 °C	ISO 3016
Colour	yellow-brown	
Flash Point	220 °C	
Total base number (TBN)	7,0 mg KOH/g	ASTM D 2896

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.