

Initial HVLP-D 46 Hydraulic Oil



BENEFITS

PRODUCT DESCRIPTION

BIZOL Initial HVLP-D 46 Hydraulic Oil is used for all kinds of hydraulic aggregates, for which the use of HVLP-D-alloyed oils is prescribed. Mineral base oils and effective zinc-containing components ensure optimum lubrication and long-lasting protection against aging.

Base Oil: Mineral

SPECIFICATIONS

DIN 51524-3 DIN 51524-3, ISO 11158, ASTM D 6158, SEB 181222



Initial HVLP-D 46 Hydraulic Oil

Available Packages

Size	Art. Nr
20 L	182282
60 L	182283
208 L	182288

Technical Data

Name	Value	Method
Viscosity at 40 °C	45,9 mm²/s	ASTM D 7042
Viscosity at 100 °C	8,1 mm²/s	ASTM D 7042
Viscosity index	150	ASTM D 2270
Density at 15 °C	874 kg/m³	DIN EN ISO 12 185
Flash Point (Cleveland)	228 °C	ISO 2592
Pour Point	-36 °C	ISO 3016
FZG Test A/8,3/90	>12	DIN 51 354/2

Follow instructions

On refilling an changing the Hydraulic Oil please follow the operating instructions of the manufacturer.