Technology 5W-30 C3

BENEFITS

- Lowered HTHS viscosity for maximum fuel economy
- Mid SAPS oil
- best cold start properties and fastest engine oiling
- extended oil change interval
- protects exhaust aftertreatment systems

PRODUCT DESCRIPTION

BIZOL Technology 5W-30 C3 is a fuel-saving , mid SAPS engine oil (gasoline, diesel) for vehicles with modern exhaust aftertreatment and extended maintenance interval. Ensures the functionality of the exhaust aftertreatment system and ensures maximum service life.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA C3, API SN

MB 229.51,229.52	BMW LL 04	VW 505 00,505 01
GM DEXOS 2	Renault RN 0700,RN 0710	

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Technology 5W-30 C3

Available Packages

Size	Art. Nr	Languages
4 L	85126	
5 L	85121	
5 L	35121	EN / DE / FR / ES / IR
60 L	85123	
200 L	85124	

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	SAE J 300
Viscosity at 40 °C	68,2 mm²/s	ASTM D 7042
Viscosity at 100 °C	11,7 mm²/s	ASTM D 7042
Viscosity index	168	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Colour	yellow-brown	
Flash Point (Cleveland)	220 °C	ISO 2592

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.