Initial HD SAE 20W-50

BENEFITS

PRODUCT DESCRIPTION

BIZOL Initial HD SAE 20W-50 is a mineral oil based aging-resistant engine oil for commercial vehicles. It provides reliable performance for the engine and is suitable for universal use.

Base Oil: Mineral

SPECIFICATIONS

ACEA E7, API CI-4, Global DHD-1, JASO DH-1

MB 228.3

Caterpillar ECF-1A,ECF-2

Detroit Diesel DDC 93K215

Allison C4

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Initial HD SAE 20W-50

Available Packages

Size	Art. Nr
20 L	186022
60 L	186023
208 L	186028

Technical Data

Name	Value	Method
Viscosity class SAE	20W-50	SAE J 300
Viscosity at 100 °C	167 mm²/s	ASTM D 7042
Viscosity at 40 °C	18,6 mm²/s	ASTM D 7042
Viscosity index	125	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Flash Point (Cleveland)	>210 °C	ISO 2592
Colour	yellow-brown	
Total base number (TBN)	11,0 mg KOH/g	ASTM D 2896

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.