

Allround 10W-40



BENEFITS

- ✓ Low oil consumption due to lower evaporation loss
- ✓ Standard SAPS
- ✓ High lubrication safety
- ✓ Extended wear and corrosion protection
- ✓ Improved engine cleanliness

PRODUCT DESCRIPTION

BIZOL Allround 10W-40 is a high-performance engine oil especially suitable for vehicles with petrol and diesel engines, with and without turbocharging. An optimal combination of base oils and additive technology improves engine performance and reduces friction and wear. Ideally suited for use in older vehicles.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA A3/B3, API SN/CF, JASO MA

MB 229.1

VW 501 01,505 00

Peugeot B71 2294

Fiat 9.55535 G2

Renault RN 0700,RN 0710

Allround 10W-40

Available Packages

Size	Art. Nr	Languages
4 L	83016	
4 L	33016	EN / DE / FR / ES / IR
5 L	83011	
5 L	33011	EN / DE / FR / ES / IR
60 L	83013	
200 L	83014	

Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	SAE J 300
Viscosity at 40 °C	94,7 mm²/s	ASTM D 7042
Viscosity at 100 °C	14,1 mm²/s	ASTM D 7042
Viscosity index	153	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-33 °C	ISO 3016
Appearance	yellow-brown	
Flash Point (Cleveland)	220 °C	ISO 2592

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.