Initial HLP 68 Hydraulic Oil

BENEFITS

PRODUCT DESCRIPTION

BIZOL Initial HLP 68 Hydraulic Oil is used for all kinds of hydraulic aggregates, for which the use of HLP-alloyed oils is prescribed. Mineral base oils and effective zinc-containing components ensure optimum lubrication and long-lasting protection against aging.

Base Oil: Mineral

SPECIFICATIONS

DIN 51524-2, ISO 11158, ASTM D 6158, SEB 181222

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Initial HLP 68 Hydraulic Oil

Available Packages

Size	Art. Nr
20 L	182212
60 L	182213
208 L	182068

Technical Data

Name	Value	Method
Viscosity at 40 °C	68 mm²/s	ASTM D 7042
Viscosity at 100 °C	8,7 mm²/s	ASTM D 7042
Viscosity index	99	ASTM D 2270
Density at 15 °C	885 kg/m³	DIN EN ISO 12 185
Flash Point (Cleveland)	250 °C	ISO 2592
Pour Point	-24 °C	ISO 3016
FZG Test A/8,3/90	>12	DIN 51 354/2

Follow instructions

On refilling an changing the Hydraulic Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.