Technology 5W-30 C2

BENEFITS

- Lowered HTHS viscosity for maximum fuel economy
- Mid SAPS oil especially for Japanese and Korean automakers
- best cold start properties and fastest engine oiling
- extended oil change interval
- protects exhaust aftertreatment systems

PRODUCT DESCRIPTION

BIZOL Technology 5W-30 C2 is a fuel-efficient, mid SAPS high-performance engine oil based on base oils of the latest technology with lowered HTHS viscosity. Specially developed for vehicles of Japanese and Korean car manufacturers.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA C2, API SN/CF, ILSAC GF 4/GF 5

Fiat 9.55535 S1

Renault RN 0700

Peugeot B71 2290

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Technology 5W-30 C2

Available Packages

Size	Art. Nr
1 L	81220
4 L	81226
5 L	81221

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	SAE J 300
Viscosity at 40 °C	64 mm²/s	ASTM D 7042
Viscosity at 100 °C	11,2 mm²/s	ASTM D 7042
Viscosity index	170	ASTM D 2270
Density at 15 °C	840 kg/m³	DIN EN ISO 12 185
Pour Point	-36 °C	ISO 3016
Flash Point (Cleveland)	224 °C	ISO 2592
ASTM colour number	L3,0	ASTM D1500
High Shear / High Temperature Viscosity	3,1 mPa,s	ASTM D 5481
Total base number (TBN)	8,2 mg KOH/g	ASTM D 2896
Sulfate ashes	0,8 %	DIN 51 575

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.