

BIZOL Technology 5W-30 Next Generation

Based on advanced synthetic technology and innovative additives, it delivers outstanding performance and reliability.

Versatile Application and perfectly suited for modern gasoline and diesel engines, including turbocharged models and those with exhaust after-treatment systems.

Can be used with:

ACEA C2/C3
API SQ (RC)/CF
ILSAC GF-7A
Fiat 9.55535-S1/S3
Fiat 9.55535-CR1
BMW Longlife-04
Chrysler MS-6395/MS-11106/MS-13340
Ford WSS-M2C929-A, Ford WSS-M2C946-A/B1, Ford WSS-M2C961-A
Ford WSS-M2C917-A
GM dexos1 Gen 3
GM dexos 2
GM 6094 M
Jaguar-Land Rover STJLR.03.5007
KIA SFU
MB 226.52 / MB 229.31 / MB 229.51 / MB 229.52
OPEL GM-LL-A-025 / OPEL GM-LL-B-025
OPEL OV 040 1547-D30
OPEL OV 040 1547-G30
Porsche C30
PSA B71 2290
PSA B71 2297
Renault RN0700
Renault RN0710
VW 502 00 / 503 01 / 505 00 / 505 01 / 504 00 / 507 00
Chinese Standard GB VI A
Chinese Standard GB VI B

Product Parameters:

Parameter	Test Method	Result
Colour	visual	brown
Kinematic Viscosity @ 40°C [mm²/s]	ASTM D-7042	73,5
Kinematic Viscosity @ 100°C [mm²/s]	ASTM D-7042	11,9
Density @ 15 °C [kg/m³]	DIN EN ISO 12185	854
Pourpoint [°C]	ISO 3016	-33
TBN [mg KOH/g]	ASTM D2896	8,3

1 Liter	Art. No. 85850
4 Liter	Art. No. 85856
5 Liter	Art. No. 85851
20 Liter	Art. No. 85852
60 Liter	Art. No. 85853
208 Liter	Art. No. 85858

BIZOL Technology 5W-30 Next Generation can be used as a substitute for the following articles:

BIZOL Allround 5W-30	81330/81336/81331/81332/81333/81334
BIZOL Technology 5W-30 507	85820/85821/85822/85823/85824
BIZOL Technology 5W-30 C2	81220/81226/81221/81222/81223/81228
BIZOL Technology 5W-30 C3	85120/85126/85121/85122/85123/85124