Allround 10W-30

BENEFITS

- Low oil consumption due to lower evaporation loss
- Standard SAPS
- High lubrication safety
- Extended wear and corrosion protection
- Improved engine cleanliness

PRODUCT DESCRIPTION

BIZOL Allround 10W-30 is a high-performance engine oil especially suitable for vehicles with petrol and diesel engines, with and without turbocharging. An optimal combination of base oils and additive technology improves engine performance and reduces friction and wear. Ideally suited for use in older vehicles.

Base Oil: Fully Synthetic

SPECIFICATIONS

API SP/CF, ILSAC GF-6A

Chrysler MS-6395

Fiat 9.55535-CR1

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Allround 10W-30

Available Packages

Size	Art. Nr
1 L	81190
4 L	81196
5 L	81191
20 L	81192
60 L	81193
208 L	81198

Technical Data

Name	Value	Method
Viscosity class SAE	10W-30	SAE J 300
Viscosity at 40 °C	74,7 mm²/s	ASTM D 7042
Viscosity at 100 °C	11,7 mm²/s	ASTM D 7042
Viscosity index	151	ASTM D 2270
Density at 15 °C	867 kg/m³	DIN EN ISO 12 185
Pour Point	-36 °C	ISO 3016
Appearance	yellow-brown	
Flash Point (Cleveland)	226 °C	ISO 2592

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.