

Allround 5W-30 A3/B4



BENEFITS

- ✓ Low-viscosity oil especially for Asian and American vehicles
- ✓ High SAPS
- ✓ Low viscosity
- ✓ Friction reduction
- ✓ Fuel economy

PRODUCT DESCRIPTION

BIZOL Allround 5W-30 A3/B4 is a low viscosity high SAPS fuel-efficient engine oil especially for gasoline engines and diesel engines.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA A3/B4, API SN/CF

MB 229.3,229.5,226.5

GM LL A-025,LL B-025

VW 502 00,505 00

Renault RN 0700,RN 0710

BMW LL 01

Allround 5W-30 A3/B4

Available Packages

Size	Art. Nr
1 L	81350
4 L	81356
5 L	81351
20 L	81352
60 L	81353
208 L	81358

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	SAE J 300
Viscosity at 40 °C	75,2 mm²/s	ASTM D 7042
Viscosity at 100 °C	12,5 mm²/s	ASTM D 7042
Viscosity index	174	ASTM D 2270
Density at 15 °C	853 kg/m³	DIN EN ISO 12 185
Pour Point	-42 °C	ISO 3016
Flash Point (Cleveland)	>210 °C	ISO 2592
Appearance	yellow-brown	
Total base number (TBN)	10,5 mg KOH/g	ASTM D 2896