

# Silicone+ L51



## BENEFITS

- ✓ effective care for plastic and rubber parts
- ✓ excellent corrosion protection
- ✓ excellent mechanical and thermal stability

### Usage



## PRODUCT DESCRIPTION

**BIZOL Silicone+ L51** is a spray to protect and lubricate plastic or rubber parts. It is moisture repellent, pH-neutral and weather resistant. It prevents freezing and drying out of rubber parts and creaking and squeaking of plastic parts providing outstanding mechanical and thermal stability. It comes with an additional spray nozzle and an extension tube in the cap.

# Silicone+ L51

## Available Packages

| Size   | Art. Nr |
|--------|---------|
| 400 ml | 80011   |

## Technical Data

| Name                     | Value                | Method |
|--------------------------|----------------------|--------|
| Basis                    | Polydimethylsiloxane |        |
| Colour                   | Transparent          |        |
| Scent                    | Characteristic       |        |
| Relative density at 20°C | 0,63 g/ml            |        |
| Refractive Index at 25°C | 1,403                |        |
| pH-Value                 | Neutral              |        |
| Temperature resistant    | -250 - +200 °C       |        |

## Applications

Spray on door seals and rubbers, creaking plastic parts, dashboards, bumpers, sunshine roofs, rails (caravan, blinds), sliding doors, saw blades, moulds.

## How to use

The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Apply silicone spray in a thin layer. Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).

## Follow instructions

Please follow the operating instructions of the vehicle and engine manufacturer.