

Technology 5W-30 C3



BENEFITS

- ✓ Lowered HTHS viscosity for maximum fuel economy
- ✓ Mid SAPS oil
- ✓ best cold start properties and fastest engine oiling
- ✓ extended oil change interval
- ✓ protects exhaust aftertreatment systems

PRODUCT DESCRIPTION

BIZOL Technology 5W-30 C3 is a fuel-saving , mid SAPS engine oil (gasoline, diesel) for vehicles with modern exhaust aftertreatment and extended maintenance interval. Ensures the functionality of the exhaust aftertreatment system and ensures maximum service life.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA C2/C3, API SN/CF

MB 229.51,229.52

GM DEXOS 2

Chrysler MS-11106

BMW LL 04

Renault RN 0700,RN 0710

Fiat 9.55535-S3

VW 502 00,505 00,505 01

Opel OV0401547-D30

Technology 5W-30 C3

Available Packages

Size	Art. Nr
1 L	85120
4 L	85126
5 L	85121
20 L	85122
60 L	85123
208 L	85124

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	SAE J 300
Viscosity at 40 °C	68,2 mm²/s	ASTM D 7042
Viscosity at 100 °C	11,7 mm²/s	ASTM D 7042
Viscosity index	168	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Colour	yellow-brown	
Flash Point (Cleveland)	220 °C	ISO 2592

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.