

# Allround Gear Oil GL5 85W-140



## BENEFITS

- ✓ very long-term oil change intervals
- ✓ for axle drives exposed to extremely high loads in commercial vehicles
- ✓ reduces running noise

## PRODUCT DESCRIPTION

**BIZOL Allround Gear Oil GL5 85W-140** is a high-performance, high-pressure gear oil. It is manufactured from carefully selected base oils and multi-functional extreme pressure additives. It is suitable for axle drives, especially heavy-duty hypoid transmissions.

**Base Oil:** Mineral

## SPECIFICATIONS

**API GL 5, MIL L-2105 D**

**DTFR** 12B100

**Volvo** 97310,97316

**ZF TE-ML**

07A,08,16B,16C,16D,17B,19B,21A

**MAN** M 342 M1

**Voith** 3.325-339

**Renault** GL-5

**Scania** STO 1:0



# Allround Gear Oil GL5 85W-140

## Available Packages

| Size  | Art. Nr |
|-------|---------|
| 20 L  | 87032   |
| 60 L  | 87033   |
| 208 L | 87034   |

## Technical Data

| Name                    | Value       | Method            |
|-------------------------|-------------|-------------------|
| Viscosity class SAE     | 85W-140     | SAE J 300         |
| Viscosity at 40 °C      | 340,0 mm²/s | ASTM D 7042       |
| Viscosity at 100 °C     | 28,0 mm²/s  | ASTM D 7042       |
| Viscosity index         | 110         | ASTM D 2270       |
| Density at 15 °C        | 910 kg/m³   | DIN EN ISO 12 185 |
| Pour Point              | <-19 °C     | ISO 3016          |
| Flash Point (Cleveland) | >200 °C     | ISO 2592          |

## Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.