Initial UNI TRUCK STOU 15W-30

BENEFITS

- Multifunctional
- High oxidation stability
- Protection against wear, corrosion and foaming

PRODUCT DESCRIPTION

BIZOL UNI TRUCK STOU 15W-30 is a modern multi-purpose oil for agricultural machinery, excavators and construction machinery and is made from Particularly manufactured from solvent-refined base oils. It is a special oil that meets the recommendations of all well-known agricultural tractor manufacturers.

Base Oil: HC-Synthetic

SPECIFICATIONS

API CG-4/SF/GL 4

Allison C4	CNH 410 B	Caterpillar TO-2
Ford ESN-M2C159-B/-C,M2C134-A	John Deere J27	Massey Ferguson CMS M 1135,CMS M 1139,CMS M 1144
Eaton M 2950S	ZF TE-ML 06B,06C,07B,07D	

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Initial UNI TRUCK STOU 15W-30

Available Packages

Size	Art. Nr
20 L	183302
60 L	183303
208 L	183308

Technical Data

Name	Value	Method
Density at 15 °C	870 kg/m³	
Viscosity at 40 °C	76,4 mm²/s	
Viscosity at 100 °C	11,8 mm²/s	
Viscosity index	150	
Total base number (TBN)	12,1 mg KOH/g	
Pour Point	-36 °C	
Flash Point	226 °C	

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.