

Protect ATF LV synt



BENEFITS

- ✓ suitable for mechanically and electronically controlled automatic transmissions
- ✓ outstanding performance at both high and low temperature extremes
- ✓ improved power transmission efficiency and smooth transmission operation

PRODUCT DESCRIPTION

BIZOL Protect ATF LV SYNT is a modern high-performance ATF for new generation automatic transmissions with low viscosity requirements. The combination of high-quality base oils and advanced additive technology ensures an excellent ageing and oxidation stability as well as superior wear protection. It allows for smooth shifting at extremely low ambient temperatures and allows for longer oil change intervals. **BIZOL Protect ATF LV SYNT** contains seal conditioner that maintain seals from ageing for optimal transmissions performance.

Base Oil: HC-Synthetic

SPECIFICATIONS

JASO 1-A-LV

Aisin Warner AW-1

MB 236.12,236.14,236.41

VW G 052 540,G 055 005,G 055 162,G 055 540,G 060 162

BMW P/N 83 22 0 142 516,P/N 83 22 2 152 426

ZF Lifeguardfluid 8

Toyota JWS 3324

Nissan Matic S,Matic W

Mitsubishi SP-IV,Dia Queen ATF J3,Dia Queen ATF-PA

Honda DW-1

Hyundai-Kia NWS 9638,SP-IV,SPH-IV,SP-IV RR

Volvo 31256675,31256774

Saab 93 165 147

DSIH 6p805

Protect ATF LV synt

Available Packages

Size	Art. Nr
1 L	29750
5 L	29751
20 L	29752
60 L	29753
208 L	29758

Technical Data

Name	Value	Method
Viscosity at 40 °C	24,2 mm²/s	DIN 51 562
Viscosity at 100 °C	5,3 mm²/s	DIN 51 562
Viscosity index	160	DIN 2909
Density at 15 °C	840 kg/m³	DIN EN ISO 12 185
Pour Point	-54 °C	ISO 3016
ASTM colour number	>L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	220 °C	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.