Green Oil+ 5W-40

BENEFITS

- Special formula for start-stop and hybrid vehicles
- Special formulation (W-Guard and COMB LubriBOOST)
- Mid SAPS oil
- excellent friction reduction and fuel economy
- excellent engine cleanliness

PRODUCT DESCRIPTION

BIZOL Green Oil+5W-40 is an innovative own development of BIZOL for vehicles with start-stop system as well as hybrid vehicles, which are strongly affected by city traffic. A combination of several unconventional base oils together with special additives ensures extremely high shear stability.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA C3, API SN/CF

MB 229.51,229.31	BMW LL 04	VW 502 00,505 00,505 01
Porsche A40	Ford WSS-M2C917-A	Renault RN 0700,RN 0710
Fiat 9.55535 S2		

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Green Oil+ 5W-40

Available Packages

Size	Art. Nr
1 L	81030
4 L	81036

Technical Data

Name	Value	Method
Viscosity class SAE	5W-40	SAE J 300
Colour	green	
Viscosity at 40 °C	80,4 mm²/s	ASTM D 7042
Viscosity at 100 °C	13,1 mm²/s	ASTM D 7042
Viscosity index	165	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Flash Point (Cleveland)	>230 °C	ISO 2592
Viscosity at -30°C	5760 mPa,s	ASTM D 5293

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.