

Green Oil+ 5W-30



BENEFITS

- ✓ Special formula for start-stop and hybrid vehicles
- ✓ Special formulation (W-Guard and COMB LubriBOOST)
- ✓ Mid SAPS oil
- ✓ excellent friction reduction and fuel economy
- ✓ excellent engine cleanliness

PRODUCT DESCRIPTION

BIZOL Green Oil+5W-30 is an innovative own development of BIZOL for vehicles with start-stop system as well as hybrid vehicles, which are strongly affected by city traffic. A combination of several unconventional base oils together with special additives ensures extremely high shear stability.

Base Oil: Fully Synthetic

SPECIFICATIONS

ACEA C3, API SN

MB 229.51,229.31

Porsche C30

BMW LL 04

Fiat 9.55535-S3

VW 504 00,507 00

Green Oil+ 5W-30

Available Packages

Size	Art. Nr
1 L	81080
4 L	81086

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	SAE J 300
Colour	green	
Viscosity at 40 °C	67 mm²/s	ASTM D 7042
Viscosity at 100 °C	11,6 mm²/s	ASTM D 7042
Viscosity index	170	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-40 °C	ISO 3016
Flash Point (Cleveland)	210 °C	ISO 2592
Total base number (TBN)	6,6 mg KOH/g	ASTM D 2896
Sulfate ashes	0,67 %	DIN 51 575
Viscosity at -30°C	5500 mPa,s	ASTM D 5293

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.