

Protect ATF DCT synt



BENEFITS

- ✓ outstanding shear stability over long maintenance intervals
- ✓ engineered for latest DCT technology
- ✓ suitable for VW DSG

PRODUCT DESCRIPTION

BIZOL Protect ATF DCT SYNT is a high-performance transmission fluid that can be used in vehicles with double clutch transmissions (DCT), e.g. VW, Audi, Seat, Skoda direct shift gearbox transmissions (DSG), Volvo, etc. To meet or even exceed the requirements of transmission manufacturers using DCT gearboxes, BIZOL applied the latest HC-technology with an excellent additives combination. **BIZOL Protect ATF DCT SYNT** ensures stable friction properties, even under hardest operating conditions.

Base Oil: HC-Synthetic

SPECIFICATIONS

DTFR 13C130

VW G 052 182,G 052 529

BMW P-N 83 22 0 440 214,P-N 83 22 2 147 477,P-N 83 22 2 148 578,P-N 83 22 2 148 579,DCTF-1

Mitsubishi MZ320065 Dia Queen SSTF-I **Porsche** Oil No.999.917.080.00

PSA 9734 S2

Volvo P/N 1161838,P/N 1161839

MB 236.25

Ford WSS-M2C936-A

Protect ATF DCT synt

Available Packages

Size	Art. Nr
1 L	27850

Technical Data

Name	Value	Method
Viscosity at 40 °C	36,4 mm²/s	DIN 51 562
Viscosity at 100 °C	7,4 mm²/s	DIN 51 562
Viscosity index	175	DIN 2909
Density at 15 °C	840 kg/m³	DIN EN ISO 12 185
Pour Point	-48 °C	ISO 3016
ASTM colour number	>L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	>190 °C	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.