

Allround Gear Oil TDL 75W-90 UNI



BENEFITS

- ✓ effective for wear reduction
- ✓ meets the requirements of modern commercial vehicles
- ✓ effective at low temperatures

PRODUCT DESCRIPTION

BIZOL Allround Gear Oil TDL 75W-90 is a fully synthetic, multi-grade gear oil for universal use. It meets almost all requirements of modern commercial vehicles regarding special lubrication for the entire drive line. TDL gear oil is perfectly suitable for lubricating all components of the drive line, from the sophisticated synchronized and non-synchronized manual gears to hypoid axle gears. Due to its characteristics as a high-performance allround product, it significantly contributes to the streamlining process in modern vehicle fleets. The reduction of friction due to optimum viscosity helps to save fuel.

Base Oil: Fully Synthetic

SPECIFICATIONS

API GL 5/GL 4, MIL L-2105 D

DTFR 12B100,13B100

BMW P/N 83 22 9 407 768

Opel 19 40 182

VW G 052 145

Ford 1 347 488

Vauxhall 93165290

MAN M 341 Z2,M 342 M2

GM 93165290

ZF TE-ML
05A,07A,12E,16B,16C,17B,19B

Allround Gear Oil TDL 75W-90 UNI

Available Packages

Size	Art. Nr
1 L	88220
20 L	88222
60 L	88223
208 L	88224

Technical Data

Name	Value	Method
Viscosity class SAE	75W-90	SAE J 300
Viscosity at 40 °C	88,0 mm²/s	DIN 51 562
Viscosity at 100 °C	15,3 mm²/s	DIN 51 562
Viscosity index	185	DIN 2909
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-42 °C	ISO 3016
Flash Point (Cleveland)	180 °C	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.