

Allround Gear Oil GL5 80W-90 UNI



BENEFITS

- ✓ high reliability of lubrication
- ✓ optimum ageing resistance
- ✓ outstanding viscosity and temperature stability

PRODUCT DESCRIPTION

BIZOL Allround Gear Oil GL5 80W-90 UNI is a multi-grade transmission oil which is resistant to temperature fluctuations and oxidation and enriched with agents for wear reduction at bearings and tooth flanks. Special additives prevent rust and foam formation.

Base Oil: Mineral

SPECIFICATIONS

API GL 5, MIL L-2105 D

DTFR 12B100

MAN M 342 M2

ZF TE-ML 05A,12E,16B,17B,19B,21A



Allround Gear Oil GL5 80W-90 UNI

Available Packages

Size	Art. Nr
1 L	89910
20 L	89912
60 L	89913
208 L	89918

Technical Data

Name	Value	Method
Viscosity class SAE	80W-90	SAE J 300
Viscosity at 40 °C	139,8	ASTM D 7042
Viscosity at 100 °C	14,2	ASTM D 7042
Viscosity index	99	ASTM D 2270
Density at 15 °C	890	DIN EN ISO 12 185
Pour Point	-30	ISO 3016
Flash Point (Cleveland)	230	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.