

Allround 5W-40



BENEFITS

- ✓ Can also be used with Gasoline/Diesel/LPG/CNG engines.
- ✓ Low-viscosity oil
- ✓ Standard SAPS
- ✓ Friction reduction
- ✓ Fuel economy

PRODUCT DESCRIPTION

BIZOL Allround 5W-40 is a fuel-saving, standard SAPS low-viscosity passenger car engine oil (petrol, diesel) with excellent cleaning properties for a wide range of vehicles with or without extended maintenance intervals.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA A3/B4, API SN/CF

MB 226.5,229.3

GM LL A-025,LL B-025

Porsche A40

BMW LL 01

Renault RN 0700,RN 0710

Peugeot B71 2296

VW 502 00,505 00

Fiat 9.55535 M2,9.55535 H2

Allround 5W-40

Available Packages

Size	Art. Nr
1 L	85220
4 L	85226
5 L	85221
20 L	85222
60 L	85223
208 L	85224

Technical Data

Name	Value	Method
Viscosity class SAE	5W-40	SAE J 300
Viscosity at 40 °C	83,2 mm²/s	ASTM D 7042
Viscosity at 100 °C	14,3 mm²/s	ASTM D 7042
Viscosity index	179	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Pour Point	-36 °C	ISO 3016
Appearance	yellow-brown	
Flash Point (Cleveland)	240 °C	ISO 2592

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.