

Initial HD SAE 15W-40



BENEFITS

- ✓ Wide range of application
- ✓ High oxidation stability

PRODUCT DESCRIPTION

BIZOL Initial HD SAE 15W-40 is a mineral oil based aging-resistant engine oil for commercial vehicles. It provides reliable performance for the engine and is suitable for universal use.

Base Oil: Mineral

SPECIFICATIONS

ACEA E7, API CI-4/SL, Global DHD-1, JASO DH-1

DTFR 15B110

Volvo VDS 3

Cummins CES 20076,CES 20077,CES 20078

MACK EO-N

Allison C4

MB 228.1

Renault Truck RLD-2

Caterpillar ECF-1A,ECF-2,TO-2

Deutz DQC III

MAN M 3275-1

MTU Type 2

Detroit Diesel DDC 93K215

Iveco 18-1804 T2 E7



Initial HD SAE 15W-40

Available Packages

Size	Art. Nr
1 L	186010
5 L	186011
20 L	186012
60 L	186013
208 L	186018

Technical Data

Name	Value	Method
Viscosity class SAE	15W-40	SAE J 300
Viscosity at 40 °C	99,2 mm²/s	ASTM D 7042
Viscosity at 100 °C	14,2 mm²/s	ASTM D 7042
Viscosity index	147	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Flash Point (Cleveland)	>210 °C	ISO 2592
Colour	yellow-brown	
Total base number (TBN)	9,5 mg KOH/g	ASTM D 2896