

Initial Premium M SAE 10W-40



BENEFITS

- ✓ highly stable lubrication film
- ✓ good cold-start performance
- ✓ effective against corrosion
- ✓ engineered for mixed fleets

PRODUCT DESCRIPTION

BIZOL Initial Premium M SAE 10W-40 is a modern high-performance, low-friction motor oil. Modern technology in combination with unique base oils provides this product with its outstanding characteristics such as reduced friction and wear protection and helps prolonging the intervals between oil changes.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA E7, API CI-4, Global DHD-1

DTFR 15B120

Renault VI RXD VI RXD

Detroit Diesel DDC 93K215

MACK EO-N,EO-M Plus

Volvo VDS 3

Deutz DQC IV

MAN M 3277,M 3377,M 3477

DAF Long Drain

Renault Truck RLD-2

Cummins CES 20078

MTU Type 3



Initial Premium M SAE 10W-40

Available Packages

Size	Art. Nr
20 L	186062
60 L	186063
208 L	186068

Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	SAE J 300
Viscosity at 40 °C	97,5 mm²/s	ASTM D 7042
Viscosity at 100 °C	14,8 mm²/s	ASTM D 7042
Viscosity index	155	ASTM D 2270
Density at 15 °C	855 kg/m³	DIN EN ISO 12 185
Pour Point	<-33 °C	ISO 3016
Flash Point (Cleveland)	>210 °C	ISO 2592
Colour	yellow-brown	

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.