Allround 15W-40

BENEFITS

- Low oil consumption due to lower evaporation loss
- Standard SAPS
- High lubrication safety
- Extended wear and corrosion protection
- Improved engine cleanliness

PRODUCT DESCRIPTION

BIZOL Allround 15W-40 is a high-performance engine oil especially suitable for vehicles with petrol and diesel engines, with and without turbocharging. An optimal combination of base oils and additive technology improves engine performance and reduces friction and wear. Ideally suited for use in older vehicles.

Base Oil: Mineral

SPECIFICATIONS

ACEA A3/B4/E2, API SJ/CF-4

MB 228.1,229.1	VW 501 01,505 00	MAN M 271
Volvo VDS	MTU Type 1	Caterpillar TO-2
Allison C4	Valtra E	

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Allround 15W-40

Available Packages

Size	Art. Nr
1 L	82010
4 L	82016
5 L	82011
20 L	82012
60 L	82013
208 L	82014

Technical Data

Name	Value	Method
Viscosity class SAE	15W-40	SAE J 300
Viscosity at 40 °C	108 mm²/s	ASTM D 7042
Viscosity at 100 °C	15,8 mm²/s	ASTM D 7042
Viscosity index	156	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-33 °C	ISO 3016
Flash Point (Cleveland)	220 °C	ISO 2592
Colour	yellow-brown	

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.