Initial CLP 320

PRODUCT DESCRIPTION

BIZOL gear oil CLP 320 is a high-quality gear oil based on mineral oil, formulated with lead-free high-pressure additives (EP additives).
Its special combination of active ingredients achieves a very good, stable high-pressure absorption capacity under impact loads.220

Base Oil: Mineral

SPECIFICATIONS

DIN 51 517 Part 3/CLP, FZG-Test A8, 3/90 FZG-Test A8, 3/90

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Initial CLP 320

Available Packages

Size	Art. Nr
20 L	184402
60 L	184403
208 L	184408

Technical Data

Name	Value	Method
Viscosity at 40 °C	328 mm²/s	ASTM D 7042
Viscosity at 100 °C	24,3 mm²/s	ASTM D 7042
Viscosity index	95	DIN 2909
Density at 15 °C	905 kg/m³	DIN EN ISO 12 185
Flash Point (Cleveland)	244 °C	ISO 2592
Pour Point	-9 °C	ISO 3016

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.