

Allround Gear Oil MTF 75W



BENEFITS

- ✓ pressure-stable lubrication protection even at hot temperatures
- ✓ excellent protection against oxidation and thermal stress
- ✓ excellent wear protection with high fuel saving potential

PRODUCT DESCRIPTION

BIZOL Allround Gear Oil MTF 75W is an HC synthetic oil for manual transmissions with the latest additive technology. It is suitable for a wide range of materials in gearboxes and meets the specifications of API GL-4. **BIZOL Allround Gear Oil MTF 75W** was especially developed for manual gearboxes and double clutch gearboxes (S tronic and DSG). It offers best fuel saving potential as well as excellent shear stability and optimum wear protection.

Base Oil: HC-Synthetic

SPECIFICATIONS

API GL 4

Honda Special Gear Oil , MTF 94

MB 235.10

PSA B71 2330

Honda MTF,MTF-II

VW G 009 317,G 052 171,G 052 178,G 052 512,G 052 726,G 50

Ford WSD-M2C200-C,WSS-M2C200-D2

BMW MTF LT-2,MTF LT-3

GM 1940182,1940764,1940768

Volvo 97308,97309



Allround Gear Oil MTF 75W

Available Packages

Size	Art. Nr
1 L	88920
20 L	88922
60 L	88923
208 L	88928

Technical Data

Name	Value	Method
Viscosity class SAE	75W	SAE J 300
Viscosity at 40 °C	54,3 mm²/s	ASTM D 7042
Viscosity at 100 °C	9,4 mm²/s	ASTM D 7042
Viscosity index	157	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	-42 °C	ISO 3016
Flash Point	215 °C	

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.