

Protect ATF CVT synt



BENEFITS

- ✓ engineered for latest CVT technology
- ✓ proper friction characteristics even under extreme operating conditions
- ✓ fuel saving potential

PRODUCT DESCRIPTION

BIZOL Protect ATF CVT SYNT is a high-performance automatic transmission fluid developed specially for the latest generation of Continuously Variable Transmission (CVT) gear boxes. Selected base oils and a well-adjusted additive package protect against foam formation, which is very important for CVT gear boxes. The product has excellent anti-aging and anti-oxidation characteristics. **BIZOL Protect ATF CVT SYNT** is suitable for the use in Autotronic gear boxes of the Mercedes A-and-B Class. It is also applicable in many variable automatic transmissions of different manufacturers, among others in Audi Multitronic.

Base Oil: HC-Synthetic

SPECIFICATIONS

MB 236.20

Mitsubishi Dia Queen NS-2,CVTF-J1,CVTF-J4,ATF SP-III

Hyundai/Kia SP-III

Toyota CVT-TC,CVT Fluid FE

Mini cooper EZL 799A

GM DEX-CVT

VW G 052 180,G 052 516

Nissan NS-1,NS-2,NS-3

Hyundai Genuine CVTF

Daihatsu Ammix CVT Fluid DC,Ammix CVT Fluid DFE

Dodge Jeep Chrysler NS-2,Jeep Chrysler Mopar CVT+4

Honda HMMF,HCF2

Suzuki TC,NS-2,CVT,CVT Green 1,CVT Green 2,sCVT Fluid

Subaru NS-2 CVT,Lineartronic CVTF,iCVT FG

Mazda JWS 3320

Ford CVT 23,CVT 30,Mercon C,WSS-M2C-928-A,WSS-M2C-933-A

Protect ATF CVT synt

Available Packages

Size	Art. Nr
1 L	27130
20 L	27132
60 L	27133
208 L	27138

Technical Data

Name	Value	Method
Viscosity at 40 °C	36,0 mm²/s	DIN 51 562
Viscosity at 100 °C	7,0 mm²/s	DIN 51 562
Viscosity index	160	DIN 2909
Density at 15 °C	848 kg/m³	DIN EN ISO 12 185
Pour Point	-45 °C	ISO 3016
ASTM colour number	>L8,0	ASTM D1500
Flash Point (Cleveland)	>195 °C	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.