

Protect ATF DIII+



BENEFITS

- ✓ optimum friction characteristics ensure reliable operation
- ✓ outstanding fluidity at low temperatures
- ✓ excellent high temperature protection

PRODUCT DESCRIPTION

BIZOL Protect ATF DIII+ is an universal automatic transmission oil. This oil is used in automatic gearboxes of passenger cars, trucks, buses and special vehicles as well as in hydraulic converters, hydraulic power steering systems and hydraulic clutches. High-quality base oil and selected additives in **BIZOL Protect ATF DIII+** ensure excellent driving properties even under heavy loads. Particularly worth mentioning is the good compatibility with various sealing materials.

Base Oil: HC-Synthetic

SPECIFICATIONS

GM Dexron III H, Ford Mercon

DTFR 13C100,13C120,13C140,13C170	MB 236.5,236.6
Allison C4	Caterpillar TO-2
Volvo 97340,97341	Voith 55.6335.XX (G607)
ZF TE-ML 09A,TE-ML 09B	

Ford ESP-M2C 166 H,ESP-M2C 138 CJ
MAN M 339 V1,M 339 Z1
ZF TE-ML 02F,03D,04D,11A,11B,14A,17C

Protect ATF DIII+

Available Packages

Size	Art. Nr
1 L	22850
20 L	22852
60 L	22853
208 L	22858

Technical Data

Name	Value	Method
Viscosity at 40 °C	36,5 mm²/s	ASTM D 7042
Viscosity at 100 °C	7,4 mm²/s	ASTM D 7042
Viscosity index	174	ASTM D 2270
Density at 15 °C	860 kg/m³	DIN EN ISO 12 185
Pour Point	<-51 °C	ISO 3016
ASTM colour number	>L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	200 °C	ISO 2592

Follow instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.