Allround 5W-20

BENEFITS

- Low-viscosity oil especially for Asian and American vehicles
- Standard SAPS
- Low viscosity
- Friction reduction
- Fuel economy

PRODUCT DESCRIPTION

BIZOL Allround 5W-20 is a low viscosity, standard SAPS fuel-efficient engine oil especially for gasoline engines of Asian and American vehicles. It minimizes the risk of low-speed pre-ignition (LSPI) and reduces wear during cold engine start.

Base Oil: HC-Synthetic

SPECIFICATIONS

API SQ (RC), ILSAC GF-7A

GM DEXOS 1 Gen. 3

Chrysler MS-6395

Ford WSS-M2C-945-B1,WSS-M2C-960-A1

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.

Allround 5W-20

Available Packages

Size	Art. Nr
1 L	84420
4 L	84426
5 L	84421
20 L	84422
60 L	84423
208 L	84428

Technical Data

Name	Value	Method
Viscosity class SAE	5W-20	SAE J 300
Viscosity at 100 °C	8,6 mm²/s	ASTM D 7042
Viscosity at 40 °C	48,5 mm²/s	ASTM D 7042
Viscosity index	156	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Pour Point	-45 °C	ISO 3016
Colour	yellow-brown	
Flash Point (Cleveland)	225 °C	ISO 2592

The statements made in this document are made according to our current knowledge. They do not absolve the user from conducting his or her own examinations. A legally binding assurance of certain properties or suitability for specific use cannot be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed personally by the user of our products.