BIZOL Pro Grease LT LX 03 Long Term

Martin-Buber-Straße 12, 14163 Berlin, Germany www.bizol.com

Ver. 2022-10-07

Description du produit

BIZOL PRO Grease LT LX 03 Long Term is a special grease with synthetic base oil and EP additives for roller and plain bearings at highest loads. Due to its reliable lubricating performance it is extremely well suited for highly loaded bearings, unfavorable operating conditions and extended relubricating periods. Due to its extremely adherent lubricating film its application is especially advantageous for machines and vehicles in the construction industry, including cement, gravel plants and quarries, as well as in agriculture. When applied on normally loaded bearings, the relubrication periods may be significantly extended. Operating temperature range: -30°C - +150°C

Spécifications / Approbations et recommandations

NLGI class 2 | DIN 51 825 | KP 2N-30 | ISO L-XCDBH 2/DIS 6743-9

Forfaits disponibles

Données techniques

Prénom	Valeur	Méthode

Instructions

On refilling and changing the grease please follow the operating instructions of the manufacturer.

Les déclarations faites dans ce document sont faites en fonction de nos connaissances actuelles. Ils ne dispensent pas l'utilisateur de mener ses propres examens. Une assurance juridiquement contraignante de certaines propriétés ou de l'aptitude à un usage spécifique ne peut être déduite de nos déclarations. Il est possible que les lois et règlements en vigueur concernant la manipulation et l'utilisation de nos produits soient observés personnellement par l'utilisateur de nos produits.