

## Benefits

1. very good anti-ageing and chemical stability
2. protects against clutch wear
3. promotes smooth shifting

## Product Description

**BIZOL Protect ATF DIII** is a high-quality transmission fluid for automatic gearboxes, hydraulic clutches and power-steerings for which ATF of the type Dexron III G, Dexron II D or TASA is recommended.

## Base Oil

HC-Synthetic



## Specifications/Approvals & Recommendations

GM Dexron III G/Dexron II D/Dexron TASA | Ford Mercon 2004  
MB 236.9 | MAN M 339 V1/M 339 Z1 | Volvo 97340/97341 |  
Voith H55.6335.XX | Allison C4 | ZF TE-ML 03D/04D/14A/17C

## Available Packages

1 L Art. 87110    5 L Art. 87111    20 L Art. 87112    200 L Art. 87114

## Technical Data

Name	Value	Method
Viscosity at 40 °C	35,7 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	7,2 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	170	ASTM D 2270
Density at 15 °C	860 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	<-39 °C	ISO 3016
ASTM colour number	> L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	200 °C	ISO 2592

## Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.