

Benefits

1. provides greater transmission life
2. can be used universally
3. suitable for all DEXRON III requirements

Product Description

BIZOL Allround ATF D-III+ is a transmission fluid for automatic gearboxes and hydraulic clutches that require an ATF Dexron III specification. This product ensures a proper functionality even under extreme operating conditions and considerable temperature fluctuations.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

GM Dexron III G/Dexron III H/Dexron II D/Dexron TASA
Ford Mercon | MB 236.1/236.5/236.6/236.7/236.9/236.10 |
MAN M 339 V2/M 339 Z2 | Volvo 97340/97341 | Allison C4/TES 389 |
ZF TE-ML 02F/03D/04D/09/11A/11B/14A/14B/16L/17C

Available Packages

1 L Art. 22840

5 L Art. 22841

Technical Data

Name	Value	Method
Viscosity at 40 °C	35,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	7,0 mm ² /s	ASTM D 7042
Viscosity index	175	ASTM D 2270
Density at 15 °C	860 kg/m ³	DIN EN ISO 12 185
Pour Point	<-40 °C	ISO 3016
ASTM colour number	L3,0	ASTM D1500

Technical Data

Name	Value	Method
Flash Point (Cleveland)	205 °C	ISO 2592

Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.