

## Benefits

1. outstanding viscosity and temperature stability
2. high reliability of lubrication
3. optimum ageing resistance

## Product Description

**BIZOL Technology Gear Oil GL5 80W-90** is a multi-grade transmission oil which is resistant to temperature fluctuations and oxidation and enriched with agents for wear reduction at bearings and tooth flanks. Special additives prevent rust and foam formation.



## Base Oil

Mineral

## Specifications/Approvals & Recommendations

API GL 5 | MIL

MB 235.0 | MAN M 342 M1 | Volvo 97310/97316 | Voith 3.325-339 |

Renault GL-5 | ZF TE-ML 07A/08/16B/16C/16D/17B/19B/21A

## Available Packages

20 L Art. 87011

200 L Art. 87013

## Technical Data

Name	Value	Method
Viscosity class SAE	80W-90	
Viscosity at 40 °C	140,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	14,3 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	100	ASTM D 2270
Density at 15 °C	900 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-24 °C	ISO 3016

## Technical Data

Name	Value	Method
Flash Point (Cleveland)	200 °C	ISO 2592

## Instructions

Please follow the operating instructions of vehicle and transmission manufacturers.