

Benefits

1. engineered for latest CVT technology
2. proper friction characteristics even under extreme operating conditions
3. excellent wear protection
4. fuel saving potential

Product Description

BIZOL Technology ATF CVT is a high-performance automatic transmission fluid developed specially for the latest generation of Continuously Variable Transmission (CVT) gear boxes. Selected base oils and a well-adjusted additive package protect against foam formation, which is very important for CVT gear boxes. The product has excellent anti-aging and anti-oxidation characteristics. **BIZOL Technology ATF CVT** is suitable for the use in Autotronic gear boxes of the Mercedes A-and-B Class. It is also applicable in many variable automatic transmissions of different manufacturers, among others in Audi Multitronic.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

MB 236.20 | VW G 052 180/G 052 516 | Toyota CVTF TC/CVTF FE |
Mitsubishi CVTF-J1/SP-III | Nissan NS1/NS2/NS3 |
Suzuki CVTF TC/NS-2/CVT Green 1 | Mini cooper EZL 799 |
Hyundai SP-CVT III | Honda HMMF/HCF2 |
Subaru CV-30/CVTF-II/High Torque CVTF/ECVT/iCVT |
Daihatsu Ammix CVT | GM DEX-CVT | Kia SP-CVT III

Available Packages

1 L Art. 27820

20 L Art. 27822

Technical Data

Name	Value	Method
Viscosity at 40 °C	34,0 mm ² /s	ASTM D 7042

Technical Data

Name	Value	Method
Viscosity at 100 °C	7,2 mm ² /s	ASTM D 7042
Viscosity index	185	ASTM D 2270
Density at 15 °C	851 kg/m ³	DIN EN ISO 12 185
Pour Point	<-40 °C	ISO 3016
ASTM colour number	> L8,0 (red)	ASTM D1500
Flash Point (Cleveland)	200 °C	ISO 2592

Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.