

## Vorteile

1. developed for year round use
2. especially developed for racing and ideally suited for motorcycles
3. optimum lubrication even under extreme conditions

## Produkt-Beschreibung

**BIZOL Technology 10W-60** is a fully synthetic, high-performance engine oil. The synthetic components give it an extremely high quality level that is particularly useful for engines that are exposed to high thermal stress.

## Basisöl

Vollsynthetisch

## Spezifikationen/Genehmigungen & Empfehlungen

API SL/CF | JASO MA-2

## Verfügbare Pakete

1 L  
Art. 89310

## Technische Daten

Name	Wert	Methode
Viscosity class SAE	10W-60	SAE J 300
Viscosity at 40 °C	164,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	23,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	170	ASTM D 2270
Density at 15 °C	850 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-39 °C	ISO 3016
Flash Point (Cleveland)	220 °C	ISO 2592
ASTM colour number	L5,0	ASTM D1500



## Technische Daten

Name	Wert	Methode
Sulfate ashes	0,90 %	DIN 51 575
Total base number (TBN)	8,2 mg KOH/g	ASTM D 2896

## Anweisungen

Beim Nachfüllen und Wechseln des Motoröls beachten Sie bitte die Betriebsanleitung des Herstellers.