

## Benefits

1. reduces running noise
2. very long-term oil change intervals
3. for axle drives exposed to extremely high loads in commercial vehicles

## Product Description

**BIZOL Technology Gear Oil GL5 85W-140** is a high-performance, high-pressure gear oil. It is manufactured from carefully selected base oils and multi-functional extreme pressure additives. It is suitable for axle drives, especially heavy-duty hypoid transmissions.



## Base Oil

Mineral

## Specifications/Approvals & Recommendations

API GL 5 | MIL L-2105 D

MB 235.0 | MAN M 342 M1 | Renault GL-5 | Volvo 97310/97316 |

Voith 3.325-339 | ZF TE-ML 07A/08/16B/16C/16D/17B/19B/21A

## Available Packages

20 L Art. 87022

200 L Art. 87024

## Technical Data

Name	Value	Method
Viscosity class SAE	85W-140	
Viscosity at 40 °C	340,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	28,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	94	ASTM D 2270
Density at 15 °C	910 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	<-19 °C	ISO 3016

## Technical Data

Name	Value	Method
Flash Point (Cleveland)	>200 °C	ISO 2592

## Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.