

## Benefits

1. very good anti-ageing and chemical stability
2. best temperature/viscosity properties
3. reduces wear and running noise

## Product Description

**BIZOL Protect Gear Oil GL4 80W-90** is a mineral high-performance transmission oil for use in spur, bevel as well as worm gears. This product is utilized in synchronized and non-synchronized manual transmissions, driving gears of construction and agricultural machinery as well as tractors.



## Base Oil

Mineral

## Specifications/Approvals & Recommendations

API GL 4

MB 235.1 | MAN M 341 E1 | ZF TE-ML 06L/08/16A/17A/19A/19C

## Available Packages

1 L Art. 87310    4 L Art. 87316    20 L Art. 87312    200 L Art. 87314

## Technical Data

Name	Value	Method
Viscosity class SAE	80W-90	
Viscosity at 40 °C	140,0 mm <sup>2</sup> /s	ASTM D 7042
Viscosity at 100 °C	14,5 mm <sup>2</sup> /s	ASTM D 7042
Viscosity index	102	ASTM D 2270
Density at 15 °C	880 kg/m <sup>3</sup>	DIN EN ISO 12 185
Pour Point	-30 °C	ISO 3016
Flash Point (Cleveland)	200 °C	ISO 2592

## Instructions

On refilling and changing the motor/gear oil please follow the operating instructions of the manufacturer.