

Benefits

1. developed especially for most cars of the GM group, where DEXOS 1 is required
2. unique dispersion properties ensure excellent cleaning properties of all engine components
3. reliable wear protection

Product Description

BIZOL Technology 5W-20 is a modern engine oil based on synthesis technology. The combination of base oils and special additive components results in a motor oil with reduced exhaust emissions and fuel saving properties. **BIZOL Technology 5W-20** provides a fast lubrication of the engine that significantly reduces wear in the cold start period.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

API SN | ILSAC GF 4/GF 5

Chrysler MS-6395 | Ford WSS-M2C-945-A/WSS-M2C-946-A |

GM DEXOS 1/6094 M

Available Packages

1 L Art. 84410

5 L Art. 84411

Technical Data

Name	Value	Method
Viscosity class SAE	5W-20	
Viscosity at 40 °C	46,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	8,3 mm ² /s	ASTM D 7042
Viscosity index	160	ASTM D 2270
Density at 15 °C	850 kg/m ³	DIN EN ISO 12 185
Pour Point	<-33 °C	ISO 3016

Technical Data

Name	Value	Method
Flash Point (Cleveland)	>200 °C	ISO 2592
ASTM colour number	L2,0	ASTM D1500
High Shear / High Temperature Viscosity	2,6 mPa,s	ASTM D 5481
Total base number (TBN)	6,0 mg KOH/g	ASTM D 2896
Sulfate ashes	0,90 %	DIN 51 575

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.