

Benefits

1. optimum engine cleanliness leads to reduced CO2 emissions
2. stable lubricating film under aggravated operating conditions
3. suitable for LPG / CNG engines

Product Description

BIZOL Allround 10W-40 is a high-performance, low friction engine oil manufactured using the latest additive technology and synthetic components. It is suitable for all year-round use in passenger cars with gasoline and diesel engines with or without turbochargers and charge-air coolers. Also suitable for LPG/CNG engines according to the manufacturer's instructions.



Base Oil

HC-Synthetic

Specifications/Approvals & Recommendations

ACEA A3/B3 | API SN/CF | JASO MA
MB 229.1 | VW 501 01/505 00 | Renault RN 0700 | Peugeot B71 2294 |
Fiat 9.55535 G2

Available Packages

1 L	1 L	4 L	4 L	
Art. 33010	Art. 83010	Art. 83016	Art. 33016	
5 L	5 L	20 L	60 L	200 L
Art. 83011	Art. 33011	Art. 83012	Art. 83013	Art. 83014

Technical Data

Name	Value	Method
Viscosity class SAE	10W-40	SAE J 300
Viscosity at 40 °C	88,5 mm ² /s	ASTM D 7042
Viscosity at 100 °C	13,3 mm ² /s	ASTM D 7042
Viscosity index	151	ASTM D 2270

Technical Data

Name	Value	Method
Density at 15 °C	870 kg/m ³	DIN EN ISO 12 185
Pour Point	-36 °C	ISO 3016
Flash Point (Cleveland)	220 °C	ISO 2592
ASTM colour number	L3,5	ASTM D1500
Evaporation loss	9,2 %	DIN 51 581
Total base number (TBN)	9,0 mg KOH/g	ASTM D 2896

Instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.