



Korzyści

1. best protection against corrosion
2. resistant to aging
3. reliable wear protection

Opis produktu

BIZOL Protect 15W-40 is a mineral based engine oil that meets the latest requirements of the automotive industry. It can be used in cars with diesel engines without DPF. Reliable base oils in combination with the latest additive technology have produced an engine oil that withstands the stress of a modern diesel engine under all operating conditions. The product neutralizes negative influences of fuel, reduces friction and wear, and prevents sludge formation.

Olej bazowy

Minerał

Specyfikacje/Aprobaty i zalecenia

ACEA A3/B3/B2/E3 | API SL/CG-4

MB 228.3 | MAN M 3275-1 | Deutz DQC-II-05 | Caterpillar ECF-1A | Volvo VDS II | Renault RD/RD-2 | MTU Type 2 |

Scania LDF | Tedom 258-3

Dostępne pakiety

Dane techniczne

Nazwa	Wartość	Metoda
Viscosity class SAE	15W-40	SAE J 300
Viscosity at 40 °C	92,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	13,3 mm ² /s	ASTM D 7042
Viscosity index	145	ASTM D 2270
Density at 15 °C	871 kg/m ³	DIN EN ISO 12 185
Pour Point	-33 °C	ISO 3016
Flash Point (Cleveland)	217 °C	ISO 2592
ASTM colour number	L3,0	ASTM D1500
Evaporation loss	7,7 %	DIN 51 581
Total base number (TBN)	9,0 mg KOH/g	ASTM D 2896
Sulfate ashes	1,40 %	DIN 51 575

Instrukcje

Przy uzupełnianiu i wymianie oleju silnikowego należy przestrzegać instrukcji obsługi producenta.