



Korzyści

1. best protection against corrosion
2. stabilny film smarowy w zastrzonych warunkach pracy
3. long-lasting protection from oil sludge formation

Opis produktu

BIZOL Protect 10W-40 UNI is a universal mineral engine oil for all types of modern turbocharged and non-turbocharged diesel and gasoline engines with or without catalytic converter. The latest additive technology in combination with high-quality base oils ensures excellent protection against oxidation, wear, improved protection against foaming, and has anti-corrosive and purifying properties. It offers these unique properties under all operating conditions, even when extended oil change intervals are required. This product is ideally suitable for mixed fleets.

Olej bazowy

Minerał

Specyfikacje/Aprobaty i zalecenia

ACEA A3/B4/E2 | API SL/CF-4 | JASO MA
MB 228.1 |

VW 501 01/505 00 | MAN M 271 | Volvo VDS

Dostępne pakiety

Dane techniczne

Nazwa	Wartość	Metoda
Viscosity class SAE	10W-40	SAE J 300
Viscosity at 40 °C	84,0 mm ² /s	ASTM D 7042
Viscosity at 100 °C	12,7 mm ² /s	ASTM D 7042
Viscosity index	149	ASTM D 2270
Density at 15 °C	870 kg/m ³	DIN EN ISO 12 185
Pour Point	-33 °C	ISO 3016
Flash Point (Cleveland)	>240 °C	ISO 2592
ASTM colour number	L3,5	ASTM D1500
Evaporation loss	9,0 %	DIN 51 581
Total base number (TBN)	9,0 mg KOH/g	ASTM D 2896
Sulfate ashes	0,80 %	DIN 51 575

Instrukcje

Przy uzupełnianiu i wymianie oleju silnikowego należy przestrzegać instrukcji obsługi producenta.