



BIZOL Green Oil 5W-40 is a unique motor oil of the latest generation based on HC-Synthesis. Through the application of unique technologies German engineers were able to develop an innovative product for the latest types of gasoline, diesel and turbo diesel engines. It perfectly protects against wear, especially under city traffic conditions. Due to its unique technology **BIZOL Green Oil 5W-40** provides the highest oil stability for the whole life cycle of the engine. Its good wear protection and lubrication properties remain unchanged even under extreme operating conditions. The green color of this product is an indicator for its incomparable technology and unique additives.

BENEFITS

- unique dispersing properties ensure the highest level of engine cleanliness, particularly in urban traffic
- outstanding cleaning properties of all engine components
- excellent anti-wear and corrosion treatment

SPECIFICATIONS

ACEA A3 / B4

API SN / CF

APPROVALS / RECOMMENDATIONS

AUDI/VW/SEAT/SKODA

VW 502 00 / 505 00

BMW

LL-01

FIAT

9.55535 H2 / 9.55535 M2 / 9.55535 N2

GENERAL MOTORS/OPEL

GM LL B-025

MERCEDES BENZ

MB 229.5

PEUGEOT/CITROËN

PSA B71 2296

PORSCHE

A40

RENAULT

RN 0700 / 0710

TECHNICAL DATA

Characteristics	Measurements	Method
Flash Point (Cleveland)	215 °C	DIN ISO 2592
Viscosity at 100°C	13,8 mm ² /s	DIN 51 562
Viscosity at -30°C	3500 mPas	DIN 51 562
Viscosity class SAE	5W-40	
ASTM colour number	>8,0	ASTMD 1500
Viscosity at 40°C	81 mm ² /s	DIN 51 562
Viscosity index	176	DIN ISO 2909
Pour Point	-33 °C	DIN ISO 3016
Colour	green	
Evaporation loss	9,1 %	
Density at 15 °C	0,860 g/cm ³	DIN 51 757
Sulfate ashes	1,3 %	DIN 51575
TBN	11,5 mgKOH/g	DIN ISO 3771

AVAILABLE PACK SIZE, ARTICLE

1L	ART. 81040
4L	ART. 81046

INSTRUCTIONS

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.