

Technology 5W-30 507



BENEFITS

- ✓ Lowered HTHS viscosity for maximum fuel economy
- ✓ Mid SAPS oil
- ✓ best cold start properties and fastest engine oiling
- ✓ extended oil change interval
- ✓ protects exhaust aftertreatment systems

PRODUCT DESCRIPTION

BIZOL Technology 5W-30 507 is a highly advanced, fuel-efficient, mid SAPS passenger car engine oil (gasoline, diesel) for vehicles with modern exhaust aftertreatment and longlife service interval. Ensures the functionality of the Exhaust aftertreatment system and ensures maximum service life.

Base Oil: HC-Synthetic

SPECIFICATIONS

ACEA C3, API SN

VW 504 00,507 00

Porsche C30

MB 229.51

Fiat 9.55535-S3

BMW LL 04

Technology 5W-30 507

Available Packages

Size	Art. Nr
1 L	85820
5 L	85821
20 L	85822
60 L	85823
208 L	85824

Technical Data

Name	Value	Method
Viscosity class SAE	5W-30	SAE J 300
Viscosity at 40 °C	67,1 mm²/s	ASTM D 7042
Viscosity at 100 °C	11,6 mm²/s	ASTM D 7042
Viscosity index	169	ASTM D 2270
Density at 15 °C	850 kg/m³	DIN EN ISO 12 185
Colour	yellow-brown	
Pour Point	-42 °C	ISO 3016
Flash Point (Cleveland)	230 °C	ISO 2592

Follow instructions

On refilling and changing the Engine Oil please follow the operating instructions of the manufacturer.