

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**Bizol Diesel Power Boost**

**UFI:**

**DSH8-80AS-F00C-3AQ0**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Additive for mineral oil products

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

Bizol Germany GmbH  
Martin-Buber-Straße 12  
14163 Berlin  
Germany

Telephone no. +49 (0) 30 80 48 69-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

+353 1 809 2166 (National Poisons Information Centre)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

Asp. Tox. 1; H304

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS08

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)

**Hazard statement(s)**

H304

May be fatal if swallowed and enters airways.

H412

Harmful to aquatic life with long lasting effects.

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

## Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

## Precautionary statement(s)

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

## UFI:

DSH8-80AS-F00C-3AQ0

## 2.3 Other hazards

PBT assessment

No data available.

vPvB assessment

No data available.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

#### Hazardous ingredients

No	Substance name		Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration	%
1	<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)</b>			
	- 925-653-7 - 01-2119458869-15	EUH066 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 25,00 - < 50,00	wt%
2	<b>Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)</b>			
	- 920-360-0 - 01-2119448343-41	Asp. Tox. 1; H304 EUH066	>= 25,00 - < 50,00	wt%
3	<b>2-ethylhexyl nitrate</b>			
	27247-96-7 248-363-6 - 01-2119539586-27	Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Aquatic Chronic 2; H411 EUH044 EUH066	>= 10,00 - < 25,00	wt%
4	<b>hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>			
	- 918-811-1 - 01-2119463583-34	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 STOT SE 3; H336	< 5,00	wt%
5	<b>2-ethylhexan-1-ol</b>			
	104-76-7 203-234-3 - 01-2119487289-20	Eye Irrit. 2; H319 Skin Irrit. 2; H315 STOT SE 3; H335 Acute Tox. 4; H332	< 5,00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of persisting adverse effects, consult a physician.

**After inhalation**

Remove affected person from the immediate area. Ensure supply of fresh air.

**After skin contact**

In case of contact with skin wash off immediately with soap and water.

**After eye contact**

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

**After ingestion**

Do not induce vomiting - aspiration hazard. Rinse the mouth thoroughly with water. Never give anything by mouth to an unconscious person. If individual is drowsy or unconscious, place in recovery position (on left side, with head down).

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

## SECTION 5: Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing media**

Water spray jet; Foam; Carbon dioxide; Extinguishing powder

**Unsuitable extinguishing media**

High power water jet

**5.2 Special hazards arising from the substance or mixture**

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon dioxide (CO<sub>2</sub>); Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

**5.3 Advice for firefighters**

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet. Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

**6.4 Reference to other sections**

No data available.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

## Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

## General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

## Advice on protection against fire and explosion

Keep away from sources of heat and ignition.

## 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place.

### Recommended storage temperature

Value < 50 °C

### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Keep only in the original container. Protect from heat and direct sunlight.

### Incompatible products

Do not store together with: Acids; Alkalies; oxidizing agents

## 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	2-ethylhexan-1-ol	104-76-7	203-234-3
	2017/164/EU		
	2-ethylhexan-1-ol		
	WEL long-term (8-hr TWA reference period)	5,4	mg/m <sup>3</sup> 1 ppm
	<b>List of Chemical Agents and Occupational Exposure Limit Values (Code of Practice)</b>		
	2-Ethylhexan-1-ol		
	WEL long-term (8-hr TWA reference period)	5,4	mg/m <sup>3</sup> 1 ppm
	Comments	IOELV	

#### DNEL, DMEL and PNEC values

##### DNEL values (worker)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	2-ethylhexyl nitrate			27247-96-7 248-363-6	
	dermal	Long term (chronic)	systemic	1	mg/kg/day
	dermal	Long term (chronic)	local	44	µg/cm <sup>2</sup>
	inhalative	Long term (chronic)	systemic	0.35	mg/m <sup>3</sup>
2	hydrocarbons, C10, aromatics, <1% naphthalene			- 918-811-1	
	dermal	Long term (chronic)	systemic	12,5	mg/kg/day
	inhalative	Long term (chronic)	systemic	151	mg/m <sup>3</sup>
3	2-ethylhexan-1-ol			104-76-7 203-234-3	
	dermal	Long term (chronic)	systemic	23	mg/kg/day
	inhalative	Short term (acute)	local	106,4	mg/m <sup>3</sup>

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

	inhalative	Long term (chronic)	systemic	53,2	mg/m <sup>3</sup>
--	------------	---------------------	----------	------	-------------------

## DNEL value (consumer)

No	Substance name			CAS / EC no
	Route of exposure	Exposure time	Effect	Value
1	2-ethylhexyl nitrate			27247-96-7 248-363-6
	oral	Long term (chronic)	systemic	25 µg/kg/day
	dermal	Long term (chronic)	systemic	0.52 mg/kg/day
	dermal	Long term (chronic)	local	22 µg/cm <sup>2</sup>
	inhalative	Long term (chronic)	systemic	87 µg/m <sup>3</sup>
2	hydrocarbons, C10, aromatics, <1% naphthalene			- 918-811-1
	oral	Long term (chronic)	systemic	7,5 mg/kg/day
	dermal	Long term (chronic)	systemic	7,5 mg/kg/day
	inhalative	Long term (chronic)	systemic	32 mg/m <sup>3</sup>
3	2-ethylhexan-1-ol			104-76-7 203-234-3
	oral	Long term (chronic)	systemic	1,1 mg/kg/day
	dermal	Long term (chronic)	systemic	11,4 mg/kg/day
	inhalative	Long term (chronic)	systemic	2,3 mg/m <sup>3</sup>
	inhalative	Short term (acute)	local	53,2 mg/m <sup>3</sup>

## PNEC values

No	Substance name			CAS / EC no
	ecological compartment	Type		Value
1	2-ethylhexyl nitrate			27247-96-7 248-363-6
	water	fresh water		0,8 µg/L
	water	marine water		0,08 µg/L
	water	fresh water sediment		0,00074 mg/kg dry weight
	water	marine water sediment		0,00074 mg/kg dry weight
	soil	-		0,000191 mg/kg dry weight
	sewage treatment plant	-		10 mg/L
2	2-ethylhexan-1-ol			104-76-7 203-234-3
	water	fresh water		0,017 mg/L
	water	marine water		0,0017 mg/L
	water	Aqua intermittent		0,17 mg/L
	water	fresh water sediment		0,28 mg/kg
	with reference to: dry weight			
	water	marine water sediment		0,028 mg/kg
	with reference to: dry weight			
	soil	-		0,047 mg/kg
	with reference to: dry weight			
	sewage treatment plant	-		10 mg/L
	secondary poisoning	-		55 mg/kg
	with reference to: food			

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol, vapour and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. combination filter

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

Respirator EN14387-A

## Eye / face protection

Safety glasses with side protection shield (EN 166)

## Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: PVC

Material thickness 0,8 mm

Breakthrough time 4 h

## Other

Normal chemical work clothing.

Appropriate Material cotton

## Environmental exposure controls

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>	
liquid	
<b>Form/Colour</b>	
liquid	
Various, depending on coloration	
<b>Odour</b>	
No data available	
<b>pH value</b>	
No data available	
<b>Boiling point / boiling range</b>	
Value	> 160 °C
<b>Melting point/freezing point</b>	
No data available	
<b>Decomposition temperature</b>	
No data available	
<b>Flash point</b>	
Value	> 61 °C
<b>Ignition temperature</b>	
No data available	
<b>Flammability</b>	
No data available	
<b>Lower explosion limit</b>	
No data available	
<b>Upper explosion limit</b>	
No data available	
<b>Vapour pressure</b>	
No data available	
<b>Relative vapour density</b>	
No data available	

# EU safety data sheet

Trade name: Bizol Diesel Power Boost

Product no.: 1723

Current version : 1.1.0, issued: 21.03.2022

Replaced version: 1.0.1, issued: 21.03.2022

Region: IE

<b>Relative density</b>
No data available

<b>Density</b>
No data available

<b>Solubility</b>
No data available

<b>Partition coefficient n-octanol/water (log value)</b>			
----------------------------------------------------------	--	--	--

No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6

log Pow		5,24	
Method	OECD 117		
Source	ECHA		

2	2-ethylhexan-1-ol	104-76-7	203-234-3
---	-------------------	----------	-----------

log Pow		2,9	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		

<b>Viscosity</b>			
------------------	--	--	--

Value	<	20,5	mm <sup>2</sup> /s
Reference temperature		40	°C
Type	kinematic		

<b>Particle characteristics</b>			
---------------------------------	--	--	--

No data available			
-------------------	--	--	--

## 9.2 Other information

<b>Other information</b>
--------------------------

No data available.
--------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

### 10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

<b>Acute oral toxicity (result of the ATE calculation for the mixture)</b>	
----------------------------------------------------------------------------	--

No	Product Name
1	Bizol Diesel Power Boost

Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE oral > 2000 mg/kg).
----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	4150	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
2	2-ethylhexan-1-ol	104-76-7	203-234-3
LD50	>	2047	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Acute dermal toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	Bizol Diesel Power Boost		
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE dermal > 2000 mg/kg).		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA / Read across		
2	2-ethylhexan-1-ol	104-76-7	203-234-3
LD50	>	3000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Acute inhalational toxicity (result of the ATE calculation for the mixture)			
No	Product Name		
1	Bizol Diesel Power Boost		
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).		
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LC50	>	5,28	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	2-ethylhexan-1-ol	104-76-7	203-234-3
LC50	1,1	- 4,3	mg/l



# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

Duration of exposure	4 h
State of aggregation	Dust/mist
Species	rat
Method	OECD 403
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are met.

Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species		rabbit	
Method		OECD 404	
Source		ECHA / Read across	
Evaluation		non-irritant	
Evaluation/classification		Based on available data, the classification criteria are met.	
2	2-ethylhexan-1-ol	104-76-7	203-234-3
Species		rabbit	
Method		OECD 404	
Source		ECHA	
Evaluation		irritant	
Evaluation/classification		Based on available data, the classification criteria are met.	

Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species		rabbit	
Method		OECD 405	
Source		ECHA / Read across	
Evaluation		non-irritant	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	2-ethylhexan-1-ol	104-76-7	203-234-3
Species		rabbit	
Method		OECD 405	
Source		ECHA	
Evaluation		Irritating to eyes	
Evaluation/classification		Based on available data, the classification criteria are met.	

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA / Read across	
Evaluation		non-sensitizing	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	
STOT - single exposure			
No data available			
STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Aspiration hazard			
No data available			

## 11.2 Information on other hazards

### Endocrine disrupting properties

No data available.

### Other information

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
LC50		2	mg/l
Duration of exposure		96	h
Species		Danio rerio	
Method		OECD 203	
Source		ECHA	
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1
LL50		>= 2	mg/l
Duration of exposure		5	h
Species		Oncorhynchus mykiss	
Method		OECD 203	
Source		ECHA	
3	2-ethylhexan-1-ol	104-76-7	203-234-3
LC50		17,1	mg/l
Duration of exposure		96	h
Species		Leuciscus idus melanotus	
Source		ECHA	
Toxicity to fish (chronic)			
No data available			
Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	2-ethylhexyl nitrate	27247-96-7	248-363-6
EC50		>	mg/l
Duration of exposure		12,6	h
Species		Daphnia magna	
Method		OECD 202	
Source		ECHA	
2	hydrocarbons, C10, aromatics, <1% naphthalene	-	918-811-1

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

EL50	>= 3	- 10	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
<b>3</b>	<b>2-ethylhexan-1-ol</b>	<b>104-76-7</b>	<b>203-234-3</b>
EC50		39	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		

## Toxicity to Daphnia (chronic)

No data available

## Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
<b>1</b>	<b>2-ethylhexyl nitrate</b>	<b>27247-96-7</b>	<b>248-363-6</b>
EC50		1,57	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
<b>2</b>	<b>hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>	<b>-</b>	<b>918-811-1</b>
EL50	>= 1	- 3	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
<b>3</b>	<b>2-ethylhexan-1-ol</b>	<b>104-76-7</b>	<b>203-234-3</b>
EC50		11,5	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Source	ECHA		

## Toxicity to algae (chronic)

No data available

## Bacteria toxicity

No data available

## 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>hydrocarbons, C10, aromatics, &lt;1% naphthalene</b>	<b>-</b>	<b>918-811-1</b>
Type	COD		
Value		49,56	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	not readily biodegradable		
<b>2</b>	<b>2-ethylhexan-1-ol</b>	<b>104-76-7</b>	<b>203-234-3</b>
Type	aerobic biodegradation		
Value	79	- 99,9	%
Duration		2	week/s
Method	OECD 301 C		
Source	ECHA		
Evaluation	readily biodegradable		

## 12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
<b>1</b>	<b>2-ethylhexyl nitrate</b>	<b>27247-96-7</b>	<b>248-363-6</b>

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

log Pow		5,24	
Method	OECD 117		
Source	ECHA		
<b>2</b>	<b>2-ethylhexan-1-ol</b>	<b>104-76-7</b>	<b>203-234-3</b>
log Pow		2,9	
Reference temperature		25	°C
Method	OECD 117		
Source	ECHA		

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

### 14.2 Transport IMDG

The product is not subject to IMDG regulations.

### 14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU safety data sheet

**Trade name:** Bizol Diesel Power Boost

**Product no.:** 1723

**Current version :** 1.1.0, issued: 21.03.2022

**Replaced version:** 1.0.1, issued: 21.03.2022

**Region:** IE

## EU regulations

<b>Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)</b>	
According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.	
<b>REACH candidate list of substances of very high concern (SVHC) for authorisation</b>	
According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.	
<b>Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES</b>	
The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
<b>Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances</b>	
This product is not subject to Part 1 or 2 of Annex I.	

## 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

### Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH044	Risk of explosion if heated under confinement.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 782219