

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Bizol Diesel System Clean+ d60

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Additive

1.3. Details of the supplier of the safety data sheet

Company name:	BIZOL BITA Trading GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 (30) 804 869-0	Telefax: +49 (30) 804 869-2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

1.4. Emergency telephone number:

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 -
08454 24 24 24 In Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aspiration hazard: Asp. Tox. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Signal word: Danger**Pictograms:****Hazard statements**

H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P260 Do not breathe vapour.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P314 Get medical advice/attention if you feel unwell.
P405 Store locked up.
P501 Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH044 Risk of explosion if heated under confinement.
EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Results of PBT and vPvB assessment: not applicable.

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 2 of 8

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	60 - 80 %
	918-481-9	
	01-2119457273-39	
	Asp. Tox. 1; H304 EUH066	
27247-96-7	2-ethylhexyl nitrate	10 - < 25 %
	248-363-6	
	01-2119539586-2	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Aquatic Chronic 2; H302 H312 H332 H411 EUH044 EUH066	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO₂). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

No special measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect against direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
27247-96-7	2-ethylhexyl nitrate		
Worker DNEL, long-term	dermal	systemic	1 mg/kg bw/day
Worker DNEL, long-term	dermal	local	0,044 mg/cm ²
Worker DNEL, long-term	inhalation	systemic	0,35 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,52 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,087 mg/m ³
Consumer DNEL, long-term	oral	systemic	0,025 mg/kg bw/day
Consumer DNEL, long-term	dermal	local	0,022 mg/cm ²

PNEC values

CAS No	Substance	
Environmental compartment	Value	
27247-96-7	2-ethylhexyl nitrate	
Freshwater	0,0008 mg/l	
Marine water	0,00008 mg/l	
Soil	0,000191 mg/kg	

8.2. Exposure controls

Appropriate engineering controls

See chapter 7. No additional measures necessary.

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 4 of 8

Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

Eye/face protection

Eye glasses with side protection.

Hand protection

Wear suitable gloves. Recommended glove articles: DIN EN 374. Suitable material: NBR (Nitrile rubber). Breakthrough time (maximum wearing time): > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light brown
Odour:	characteristic

pH-Value:	not applicable	Test method
-----------	----------------	--------------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	145 °C
Pour point:	not determined
Flash point:	63 °C
Lower explosion limits:	0,7 vol. %
Upper explosion limits:	6,0 vol. %
Ignition temperature:	not determined
Decomposition temperature:	No information available.
Vapour pressure:	not determined
Density (at 15 °C):	0,842 g/cm ³
Water solubility:	insoluble
Partition coefficient:	not determined
Viscosity / dynamic:	not determined
Viscosity / kinematic: (at 40 °C)	< 7 mm ² /s
Flow time:	not determined
Vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 5 of 8

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	oral	LD50 >5000 mg/kg	Rat	
	dermal	LD50 >5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 >4951 mg/l	Rat	
27247-96-7	2-ethylhexyl nitrate			
	oral	LD50 >9640 mg/kg	Rat	
	dermal	LD50 4820 mg/kg	Rabbit	
	inhalative vapour	ATE 11 mg/l		
	inhalative (1 h) aerosol	LC50 >4,6 mg/l	Rat	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience

Other observations

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 6 of 8

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	
	hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201
	Acute crustacea toxicity	EC50	>1000 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202
27247-96-7	2-ethylhexyl nitrate					
	Acute fish toxicity	LC50	1,88 mg/l	96 h	Brachydanio rerio (zebra-fish)	
	Acute algae toxicity	ErC50	>12,6 mg/l	72 h		
	Acute crustacea toxicity	EC50	>12,6 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
27247-96-7	2-ethylhexyl nitrate			
	Biodegradation	0 %	28	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
27247-96-7	2-ethylhexyl nitrate	3,74 - 5,24

BCF

CAS No	Chemical name	BCF	Species	Source
27247-96-7	2-ethylhexyl nitrate	1332		

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

Waste disposal number of waste from residues/unused products

070704 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fine chemicals and chemical products not otherwise specified; other organic solvents, washing liquids and mother liquors
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 7 of 8

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine pollutant: NO

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2010/75/EU (VOC): 95 % (799,9 g/l)

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,7,9,13,14,15.

Abbreviations and acronyms

ADR: Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
CAS: Chemical Abstracts Service (a division of the American Chemical Society)
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
WEL (UK): Workplace Exposure Limits
TWA (EC): Time-Weighted Average
STEL (EC): Short Term Exposure Limit
ATE: Acute Toxicity Estimate

Bizol Diesel System Clean+ d60

Revision date: 19.07.2016

Page 8 of 8

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration

ErC50: EC50 in terms of reduction of growth rate

VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH044	Risk of explosion if heated under confinement.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)